Int'l. Application No. PCT/GB2003/003262 Preliminary Amendment Page 2

CLAIM AMENDMENTS

- 1. (Original) A pipe coupling flange comprising a central bore and having first and second ports for receiving valves and a plurality of channels, wherein a take-off channel links the first port with the central bore, a feed channel links the first port directly or indirectly with the second port; and wherein the second port links directly or indirectly with the exterior of the flange.
- 2. (Original) A pipe coupling flange as claimed in Claim 1 further comprising a third port connected directly or indirectly to the first or second port via one or more feed channels.
- 3. (Currently Amended) A pipe coupling as claimed in Claim 1 or claim 2, wherein the pipe coupling is provided with a fourth port adapted to receive a pipe joint and a feed channel connecting the third port with the fourth port.
- 4. (Currently Amended) A pipe coupling flange as claimed in Claim 1, 2, or 3, wherein the ports of the pipe coupling are adapted to receive rising stem valves.
- 5. (Currently Amended) A pipe coupling as claimed in Claim 1, 2, or 3, wherein the ports are adapted to receive in-line valves.
- 6. (Currently Amended) A pipe coupling flange as claimed in Claim 1 any one of claims 1 to 5, further comprising a transducer.
- 7. (Original) A pipe coupling flange as claimed in Claim 6, wherein the transducer is connected to an outlet channel of the pipe coupling.
- 8. (Currently Amended) A pipe coupling flange as claimed in Claim 6 or claim 7, wherein the transducer is connected directly to the pipe coupling.
- 9. (Currently Amended) A pipe coupling flange as claimed in claim 6 or claim 7, wherein the transducer is connected to the pipe coupling indirectly by way of a bridge element.

- 10. (Original) A pipe coupling flange as claimed in claim 9, wherein the bridge is manufactured of metal.
- 11. (Original) A pipe coupling flange as claimed in claim 10, wherein the bridge is manufactured of steel.
- 12. (Currently Amended) A pipe coupling flange as claimed in claim 9, 10 or 11, wherein the bridge is adapted to receive industry standard transducers.
- 13. (Currently Amended) A pipe coupling flange as claimed in claim 9 any one of claims 9 to 12, wherein the bridge incorporates an industry standard footprint for receiving a transducer.
- 14. (Currently Amended) A pipe coupling flange as claimed in Claim 1 any one of claims 1 to 13, when the flange is formed integrally with a process pipe.
- 15. (Currently Amended) A pipe coupling flange as claimed in claim 1 any one of claims 1 to 13, when the flange comprises a collar element.
- 16. (Original) A pipe coupling flange as claimed in claim 15, wherein the collar element is adapted to slidably engage with a process pipe.
- 17. (Currently Amended) A pipe coupling flange as claimed in claim 15 or claim 16, wherein the collar element is adapted for welded connection to a process pipe.
- 18. (Currently Amended) A pipe coupling assembly comprising two adjacent pipe coupling flanges as claimed in claim 1 or any one claims 2 to 17.
- 19. (Original) A pipe coupling assembly as claimed in claim 18, further comprising an orifice plate located between the adjacent pipe coupling flanges.
- 20. (Currently Amended) A pipe coupling assembly as claimed in claim 18 or claim 19, further comprising a bridge and a transducer, the bridge

23.

having channels therein for connecting at least one port of the at least one pipe coupling flanges with the inlet ports of the transducer.

- 21. (Original) A pipe coupling assembly as claimed in claim 20, wherein the transducer is a differential pressure sensor and the bridge has channels that connect at least one port of each pipe coupling flange with a respective port of the transducer.
- 22. (Original) A pipe coupling comprising of two bolted pipe flanges, rising stem type valves, an interconnecting "Bridge", an orifice plate and pipe gaskets or rings, which allows the installation of process media monitoring devices directly on to the process pipe work.
 - (Currently Amended) A kit of parts comprising;
 one or more a pipe coupling flanges comprising a pipe
 with a central bore having a flange integrally formed
 therewith, the flange having first, second and third ports for
 receiving valves and a plurality of channels, wherein a take-off
 channel links the first port with the central bore, feed channels
 link the first port directly or indirectly with the second and
 third ports; and wherein the second and third ports link directly
 or indirectly with the exterior of the flange; and

a bridge having one or more channels therein for connecting at least one port of the at least one pipe coupling flanges with a transducer.

- 24. (Original) A kit of parts as claimed in claim 23 further comprising a transducer.
- 25. (Currently Amended) A kit of parts as claimed in claim 23 or 24 comprising two pipe coupling flanges, an orifice plate and a transducer, wherein the transducer is a differential pressure sensor.
- 26. (Currently Amended) A kit of parts as claimed in any of claims 23, 24 or 25, wherein the kit of parts is assembled and tested to

Int'l. Application No. PCT/GB2003/003262 Preliminary Amendment Page 5

industry standards.

27. (Cancelled)

28. (Cancelled)

Respectfully submitted,

Allen J. Hoover

Reg. No. 24,103

Wood, Phillips, Katz, Clark & Mortimer 500 West Madison Street – Suite 3800

Chicago, Illinois 60661-2511

Telephone: (312) 876-1800 Facsimile: (312) 876-2020

January 25, 2005

005